



TF1011

POLYURETHANE BUSH KIT – FRONT RADIUS ARM TO CHASSIS

FITTING INSTRUCTIONS

Kit Contents:

- 2 x bushes
- 2 x centre sleeves
- 4 x thrust washers
- 2 x sachets of bush lubricant

Procedure:

1. Remove old bushes from the radius arm, clean arm once removed so as not to damage the bush during installation.
2. Before installing the bush in to the arm, note that the ends of each bush are a different diameter. The larger diameter end faces the outside of the vehicle.
3. Install new PU bushes in to the arm using soapy water as a lubricant if needed, this will dry off over time - **do not use the lubricant provided, this is purely to aid centre sleeve installation as this will cause the bush to rotate within the arm itself.**
4. Smear lubricant from the sachet on the centre sleeve and push all the way through the bush so the end of the sleeve is flush at each end of the bush.
5. Prior to attaching the arms to the vehicle, ensure the relevant mountings on the vehicle are clean, same applies to the retaining bolts and nuts.
6. Place a thrust washer on each end of the bush, you can use a dab of lubricant to hold them in place. You'll notice there's a recess in the end of the bush at the larger diameter end for the washer to locate in to. These thrust washers are located withing the chassis mounting on both sides and protect the bushes from wear.
7. Fit the arm to vehicle, you can smear the bolt and threads with a small amount of anti-seize compound if required, torque to factory settings before repeating for the other arm.



WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.